

# N.C MATT LACQUER

N.C Matt Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent gloss finish. Formulated as a topcoat on N.C paint systems where fast drying, hard and clear high Matt finish is required.



## PRODUCT BENEFITS



PREMIUM QUALITY



SMOOTH



MATT FINISH



FAST DRYING

## PRODUCT FEATURES

### WASHABILITY



✓ BEST IN CLASS  
HIGH  
MEDIUM  
LOW

### AVAILABLE PACKS



### PREPARATION REQUIRED



Pre-primed and smooth surface. Ensure that surface is clean, dry and clean from grease, oil and other contamination. Wood should be properly sanded and must be scuffed in the direction of wood grains. Seal with N.C Sealer



Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Seal with N.C Sealer.

### FINISH



### TECHNICAL INFORMATION

- Coverage
  - 120-140 sq.ft per Litre
- Application
  - Spray Gun
- Thinner
  - N.C Thinner
- Drying Time
  - 2-3 hours between coats
- No of Coats
  - 2-3
- Cleaning
  - Clean all equipment with Thinner
- Thinning
  - By Spray 30-40%

### SPREADING RATE

**1 COAT**  
On previously painted surfaces to get the one coat hiding up to 140 sq.ft per liter/ per coat

**2 COATS**  
On new surfaces up to 120 sq.ft per liter by two coats

### SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.