

N.C PRIMER

N.C Primer based on nitrocellulose and alkyd resins. It has an optimum balance between standability, water resistance and hold out of top coat.



PRODUCT BENEFITS



FAST DRYING



HIGH OPACITY



EASY TO APPLY



LEAD FREE

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS
HIGH
MEDIUM
LOW

AVAILABLE PACKS



0.91 Litre



3.64 Litre

PREPARATION REQUIRED



Pre-primed and smooth surface. Ensure that surface is clean, dry and clean from grease, oil and other contamination. Wood or Metal should be properly sanded and must be scuffed in the direction of woodgrains.



Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off.

FINISH



SMOOTH SHINY NORMAL LOW

✓ SMOOTH

TECHNICAL INFORMATION

- Coverage

120-140 sq.ft per Litre

- Application

Brush / Roller / Spray Gun

- Thinner

N.C Thinner

- Drying Time

30 minutes between coats

- No of Coats

2-3

- Cleaning

Clean all equipment with Thinner

- Thinning

By Brush / Roller 10-15%
By Spray Gun 25%

SPREADING RATE



2 COAT

On previously painted surfaces to get the one coat hiding up to 140 sq.ft per liter/ per coat



3 COATS

On new surfaces up to 120 sq.ft per liter by two coats

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.