

Fancy Texture Finish

Master Wall Putty water based is a marvelous quality filler. It is 100% acrylic based and used for all interior masonry surfaces such as brick work, plaster and cement rendering.



PRODUCT BENEFITS



SMOOTH FINISH



HIGH OPACITY



ANTI-FUNGAL



STAIN RESISTANT

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

FINISH



SMOOTH

SHINY

NORMAL

LOW

✓ SMOOTH

SPREADING RATE



Estimated average Coverage: 6-7 square feet per KG (single Coat)

PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. Prime with Master Under Coat and prepare the base with Master Wall Putty.



Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Prime with Master Wall Sealer and prepare the base with Master Wall Putty where needed.

AVAILABLE PACKS



6 KG



24 KG

TYPICAL SURFACES

- New or bare surfaces.
- Previously painted surfaces.

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.

TECHNICAL INFORMATION

● Coverage

2-3 m² / kg / coat

● Application

Texture Applicator

● Thinner

Clean Water

● Drying Time

3-4 hours between coats

● Cleaning

Clean all equipment with Water

● Thinning

Ready to use