

GLOSS LACQUER

Wood Master Gloss Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent gloss finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high gloss finish is required.

PRODUCT BENEFITS







PREMIUM QUALITY



LEAD FREE



FAST DRYING



HIGH OPACITY & WHITENESS



PRODUCT FEATURES

WASHABILITY



AVAILABLE PACKS



PREPARATION REQUIRED



Pre- primed and smooth surface. Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood should be properly sanded and must be scuffed in the direction of wood grains. Seal with Wood Master.



Thoroughly clean surface Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Seal with Wood Master Sealer.

FINISH



TECHNICAL INFORMATION

Coverage

140 sq.ft per Litre

Application

Spray Gun

Thinner

Wood Thinner

Drying Time

2-3 hours between coats

No of Coats

2-3

Cleaning

Clean all equipment with Thinner

Thinning

By Spray 30-40%

SPREADING RATE



SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable.

You must wear eye protection while applying paint. Always keep container air tight close.

It must be kept out of children's reach.

Incase of contact with eyes, wash with brimful cup of water and immediately approach doctor.

Always manage container to keep it in upright position.

Protect it from extreme temperatures.
Please do not empty into drain and water sources.

Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray.

In case ventilation is insufficient the use of proper respiratory equipment is advised.