

SEA SHELL MATT ENAMEL

Master Matt Enamel (Sea Shell Finish) is a high quality paint which is suitable for interior surfaces such as wood, metal, and masonry. Especially formulated and suitable for kitchens and bathrooms because of its moisture resistant quality, It is also used for interior and exterior surfaces.



PRODUCT BENEFITS



SMOOTH SEA SHELL FINISH



ANTI-FUNGAL



SUPREME QUALITY



STAIN RESISTANT



ENVIRONMENT FRIENDLY

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS
HIGH
MEDIUM
LOW

AVAILABLE PACKS



PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. After priming with Master Primer, fill surface with a mixture of 4 parts chalk, 1 part lithopone and 3-4 parts Master Primer to give it a paste like consistency. Allow the filter to dry overnight.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Spot prime and fill surface as described.

COLOURS AVAILABLE

46

Factory Made Direct Shades



FINISH



TECHNICAL INFORMATION

● Coverage

14-16 m² / liter / coat

● Application

Brush / Roller / Spray Gun

● Thinner

White Spray / Turpentine

● Drying Time

12 hours between coats

● No of Coats

2-3

● Thinning

By Roller / Brush 10-15%
By Spray 20-25%

● Cleaning

Clean all equipment with Spirit or Turpentina

SPREADING RATE



1 COAT

On previously painted surfaces to get the one coat hiding up to 100 sq.ft per liter/ per coat



2 COATS

On new surfaces up to 100 sq.ft per liter by two coats

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised. **STIR THOROUGHLY BEFORE USE.**