

# PAINT REMOVER

Master Paint Remover is a product based on methylene chloride. The product is thick fluid, but is easy to use. Paint Remover is not recommended to be used in linoleum or vinyl coating.



## PRODUCT BENEFITS



EFFECTIVELY REMOVE



CLEANING & DEGREASING




USE TO REMOVE PAINT



SOFTEN OLD PAINT

## PRODUCT FEATURES

### WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

### AVAILABLE PACKS



0.91 Litre



20 Litre

### PREPARATION REQUIRED



Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off.



The surface should be dry and free from dust and other contamination prior to use. Paint remover is most efficient at approximately 200C. Not to be exposed to temperature above 350C. Avoid inhalation of gasses.

### FINISH



SMOOTH SHINY NORMAL LOW

✓ SMOOTH

### TECHNICAL INFORMATION

● Coverage

100-110 sq.ft per Litre

● Thinning Agent

NC Thinner, Master Thinner

● Application

Brush, Putty Knife

● No of Coats

1-2

### SPREADING RATE



1 COAT

On previously painted surfaces to get the one coat hiding up to 140 sq.ft per liter/ per coat



2 COATS

On new surfaces up to 110 sq.ft per liter by two coats

### SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.