

PREMIUM THINNER

Wood Master Thinner is a high quality thinner suitable for thinning Wood Master Products. Please see Wood Master Products data sheet for respective thinning instructions.



PRODUCT BENEFITS



PREMIUM QUALITY



FAST DRYING



LEAD FREE




EXCELLENT SOLUBILITY



CLEANING & DEGREASING

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

FINISH



SUPERIOR

SHINY

NORMAL

LOW

✓ SMOOTH

SPREADING RATE



Estimated average Coverage 140 square feet per litre (Single Coat)

AVAILABLE PACKS



0.91 Litre



3.64 Litre



20 Litre

TECHNICAL INFORMATION

- Coverage

120-140 per litre / coat

- Application

Brush / Roller / Spray Gun

- Drying Time

2-3 hours between coats

- No of Coats

1-2


SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.

PREPARATION REQUIRED



Pre-primed and smooth surface. Ensure that surface is clean, dry and clean from grease, oil and other contamination. Wood should be properly sanded and must be scuffed in the direction of wood grains. Seal with Wood Master.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Seal with Wood Master Sealer.