

PRIMER RED OXIDE

Master Primer Red Oxide is a solvent based anti-corrosion protective primer for interior and exterior ferrous and non ferrous metal work including new weathered and pre-treated zinc and galvanized iron. It may also be applied over pre-treated aluminium.



PRODUCT BENEFITS



TOUGH & DURABLE



EXTRA COVERAGE




CORROSIVE RESISTANT



HEAT RESISTANT

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS
HIGH
MEDIUM
LOW

FINISH



SPREADING RATE



Estimated average Coverage: 100 square feet per Litter (single Coat)

AVAILABLE PACKS



0.91 Litre



3.64 Litre



14.56 Litre

PREPARATION REQUIRED



Surface must be clean, dry and free from all defective or poorly adhering material, dirt, grease and wax etc.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off.



New galvanized and aluminium surfaces should be cleaned and degreased, then pre-treated with an appropriate pre-treatment primer to ensure good adhesion.

TECHNICAL INFORMATION

Coverage

11-13 m² / litre / coat

Application

Brush / Roller

Thinner

White Spirit / Turpentine

Drying Time

16 hours between coats

No of Coats

1

Thinning

By Roller / Brush 10-12%

Cleaning

Clean all equipment with Turpentine

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Galvanised and aluminium surfaces

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised. **STIR THOROUGHLY BEFORE USE.**