

# SEALER WOOD MASTER

Sealer Wood Master is a protective nitrocellulose based quick drying sanding sealer. It provides smooth and excellent base to top coat application.



## PRODUCT BENEFITS



SMOOTH FLOW



FAST DRYING



PREMIUM QUALITY



LEAD FREE

## PRODUCT FEATURES

### WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

### FINISH



CLEAR SHINY NORMAL LOW

✓ SMOOTH

### SPREADING RATE



Estimated average Coverage 120-140 square feet per litre (Single Coat)

### AVAILABLE PACKS



0.91 Litre



3.64 Litre



20.0 Litre

### TECHNICAL INFORMATION

- Coverage  
120-140 sq.ft per Litre
- Application  
Spray Gun
- Thinner  
Wood Thinner
- Drying Time  
2-3 hours
- No of Coats  
1
- Cleaning  
Clean all with Wood Thinner
- Thinning  
Spray 30-40%

### TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

### SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.

### PREPARATION REQUIRED



Pre-primed and smooth surface. Ensure that surface is clean, dry and clean from grease, oil and other contamination. Wood should be properly sanded and must be sanded in the direction of wood grains.



Thoroughly clean surface. Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off.