

# SUPERIOR SYNTHETIC ENAMEL

Master Synthetic Metallic Enamel is a high gloss, high sparkle and high luster paint. It is equally good for all kinds of wood and metal surfaces. Master Synthetic Metallic Enamel gives a smooth and sparkling surface to the objects painted with it. It provides a fantastic film formation. It is based on high class synthetic resin. Available in different colour.



## PRODUCT BENEFITS



SMOOTH FLOW



ANTI-FUNGAL



SUPREME QUALITY



STAIN RESISTANT



WIDE COLOR RANGE

## PRODUCT FEATURES

### WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

### AVAILABLE PACKS



0.91 Litre



3.64 Litre




14.56 Litre

### COLOURS AVAILABLE

60

Factory Made Direct Shades



### FINISH



SUPERIOR

SMOOTH

NORMAL

LOW

✓ SMOOTH

### SPREADING RATE



2 COATS

On previously painted surfaces to get the one coat hiding up to 160sqft per liter/ per coat



3 COATS

On new surfaces up to 125 sq.ft per liter by two coats

### PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. Scuff surface using abrasive paper and dust off. Use Master Primer Red Oxide on metal surface and under coat on wooden surface and leave to dry.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Use Master Primer Red Oxide on metal surface and under coat on wooden surface and leave to dry.

### TECHNICAL INFORMATION

#### ● Coverage

14-17 m<sup>2</sup> / litre / coat

#### ● Application

Brush / Roller / Spray Gun

#### ● Thinner

White Spray

#### ● Drying Time

12 hours between coats

#### ● No of Coats

2-3

#### ● Thinning

By Roller / Brush 10-15%  
By Spray 25%

#### ● Cleaning

Clean all equipment with Spirit or Turpentine

### TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

### SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised. STIR THOROUGHLY BEFORE USE.