

SYNTHETIC VARNISH

Master Synthetic Varnish is high quality Synthetic Varnish that has no comparison because of its long lasting finish and durability. It is suitable for all types of exterior and interior wood and metal surface.



PRODUCT BENEFITS



SMOOTH FLOW



STAIN RESISTANT



HIGH GLOSS

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS
HIGH
MEDIUM
LOW


AVAILABLE PACKS



PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. After priming with Master Wall Primer, fill and smooth the surface with Master Wall Putty.



Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Spot prime and fill surface as described.

FINISH



CLEAR SHINY NORMAL LOW

✓ SMOOTH

TECHNICAL INFORMATION

- Coverage
100 sq.ft per Litre
- Application
Brush / Roller / Spray Gun
- Thinner
White Spirit
- Drying Time
12 hours between coats
- No of Coats
1
- Cleaning
Clean all equipment with White Spirit
- Thinning
By Roller / Brush / Spray 10%

SPREADING RATE



Estimated average Coverage 100 square feet per litre (Single Coat)

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Powdery dusty surfaces. (With cracks and other surface defects)

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.