

UNDER COAT

Master Synthetic Alkali Resistant sealer is a high quality wall sealer. It can be applied on all types of interior surfaces like, concrete, cement and plaster. It provides excellent protection against damages resulting from alkali.



PRODUCT BENEFITS



ANTI-FUNGAL



EXTRA COVERAGE



EXCELLENT TOPCOAT BASE



SUPERIOR WASH ABILITY

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS

HIGH

MEDIUM

LOW

FINISH



SMOOTH SMOOTH NORMAL LOW

✓ SMOOTH

SPREADING RATE



Estimated average Coverage: 100 square feet per Litre (single Coat)

AVAILABLE PACKS



0.91 Litre




3.64 Litre




14.56 Litre

PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. Prime with Master wall sealer



Thoroughly clean surface Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Prime with Master wall sealer where needed.

TECHNICAL INFORMATION

● Coverage

100 sq. ft per Litre

● Application

Brush / Roller / Spray Gun

● Solvent

White Spirit / Turpentine Oil

● Drying Time

13 hours between coats

● No of Coats

1-2

● Cleaning

Clean all equipment with Turpentine

● Thinning

By Brush / Roller 10-12%
By Spray 20-25%

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.