


WEATHER RESISTANT PRIMER

A high acrylic Water based primer suitable for plastered, masonry, pop limered or preprinted surfaces. It insures a better finish and durability of topcoat. It provides a better adhesion on the surface with excellent inter coat adhesion.



PRODUCT BENEFITS



PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS
HIGH
MEDIUM
LOW

AVAILABLE PACKS



PREPARATION REQUIRED

- Make sure that new or bare surfaces are free from efflorescent salts, properly cleaned and dried prior to salt. Rub down all defective or poorly adhering materials using a suitable abrasive paper or stiff brush and dust off. Apply Master Weather Resistant Primer and let dry for 2-3 hours.
- Areas affected by molds, lichens, or algae must be first treated with bleach. Wipe surface with bleach and water atleast 2-3 times until remains of fungus is properly cleaned. Smoothen surface by removing all defective or poorly adhering materials using a suitable abrasive paper or stiff brush and dust off.
- Surfaces with cracks or broken areas must be leveled first and polished prior to primer application. Level surface with sand and cement mixture and let dry for a day. When dried, remove any defected or poorly adhering materials using a suitable abrasive paper or stiff brush and dust off.
- For previously primed/painted surfaces, polish the surface with an abrasive paper or stiff brush from any poorly adhering materials or use a paint remover in clearing of remains of previous paint, dust off properly. Spot prime or apply Master Weather Resistant Water Based Primer throughly accordingly and let dry properly.

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Fungal infected surfaces/ Defective surfaces.


FINISH



TECHNICAL INFORMATION

- Coverage
18-20 m² / litre / coat
- Application
Brush / Roller / Spray Gun
- Thinner
Clean Water
- Drying Time
1-2 hours between coats
- No of Coats
1-2
- Thinning
Roller 20-30% / Brush 60-70%
Spray 30-40%
- Cleaning
Clean all equipment with Water

SPREADING RATE



SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable. You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach. In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position. Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray. In case ventilation is insufficient the use of proper respiratory equipment is advised.
STIR THOROUGHLY BEFORE USE.