

EXTERIOR WALL PUTTY

Master Wall Putty water-based is a marvelous quality filler. It is 100% acrylic-based and used for all interior masonry surfaces such as brick work plaster and cement rendering.



PRODUCT BENEFITS



SMOOTH
FINISH



HIGH
OPACITY



ANTI-FUNGAL




SUPREME
QUALITY



ENVIRONMENT
FRIENDLY

PRODUCT FEATURES

WASHABILITY



✓ BEST IN CLASS
HIGH
MEDIUM
LOW

FINISH



SPREADING RATE



Estimated average
Coverage: 6-7 square
feet per KG

AVAILABLE PACKS



5 KG.



20 KG.

PREPARATION REQUIRED



Surface must be clean, dry and free from efflorescent salts. Prime with Master Under Coat and prepare the base with Master Wall putty.



Thoroughly clean surface Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Prime with Master Wall Sealer and prepare the base with master wall putty where needed.

TECHNICAL INFORMATION

- Coverage
14-15 square feet per KG (single Coat)
- Application
Putty Applicator
- Thinner
Clean Water
- Drying Time
2-3 hours between coats
- No of Coats
1-2
- Cleaning
Clean all equipment with Water

TYPICAL SURFACES

- New surfaces.
- Previously painted surfaces.
- Fungal infected surfaces/
Defective surfaces.

SAFETY & ENVIRONMENTAL NOTES

Keep away from ignition sources because it is flammable.
You must wear eye protection while applying paint. Always keep container air tight close. It must be kept out of children's reach.
In case of contact with eyes, wash with brimful cup of water and immediately approach doctor. Always manage container to keep it in upright position.
Protect it from extreme temperatures. Please do not empty into drain and water sources. Use of mask is advisable while rubbing down and same is true when applying by spray never breath vapor / spray.
In case ventilation is insufficient the use of proper respiratory equipment is advised.
STIR THOROUGHLY BEFORE USE.