



Gloss Lacquer Wood Master

Material Safety Data Sheet

Wood Master Gloss Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent Gloss finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high Gloss finish is required.

**Research and Development Department
Master Paint Industries (Pvt.) Ltd.**

Phone : 0 4 2 – 111 – 333 – 465,

E-Mail : info@masterpaints.com



*Gloss Lacquer Wood Master
Data Sheet***PRODUCT INFORMATION**

Description: Wood Master Gloss Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent Gloss finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high Gloss finish is required.

Recommended Use: It is suitable for all types of wooden surfaces such as furniture, case works. Also suitable for industrial lacquer application where fast drying is the requirement.

PHYSICAL CONSTANTS:

Pack Size: 0.91 LTR ,3.64 LTR & 20.00 LTR (Pack)

Finish: High Gloss

Color Clear

Theoretical Spreading rate : 120-140sq.ft/liter/coat (25±5-microns)
depending on number of factors

Drying time: 15 min at 35 °C. Recoating time 1 hour.

Flash Point : 40 F°

Physical constants are subject to normal manufacturing tolerances

APPLICATION DETAIL :

Application Method : By Spray
Thinner : Wood Master Thinner

Thinning : With 1 part of Gloss Lacquer, use 1.5 to 2.0 part of wood master thinner by volume.

No. of Coats : 2 to 3 Coats

Typical Painting System: On Wood

TYPICAL SURFACES:

New Surfaces: Surface must be clean, dry and free from efflorescent salts. Seal with Wood Master,

Previously painted surfaces: Thoroughly clean surface Remove all defective or poorly adhering material by rubbing down using a suitable abrasive paper and dust off. Seal with Wood Master Sealer,



Use abrasive paper Dust off

Storage The product must be stored in accordance to national regulations. The product should be kept in well-ventilated place, protected from heat and direct sunlight. The containers must be kept tightly closed.

Handling Handle with care. Stir well before use.

SAFETY AND ENVIRONMENTAL NOTES:

Physical constants are subject to normal manufacturing tolerances. Keep away from ignition sources because it is flammable. If you are Non-professional please don't use large surface. Ventilation should be ensured because it contains white spirit. Always keep container air tight. Please follow all local and national safety regulations.

