



Master Paint Remover

Material Safety Data Sheet

Master Paint Remover is a product based on methylene chloride. The product is a thick fluid, but is easy to use. Paint Remover is not recommended to be used in linoleum or vinyl coating.

Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com



PRODUCT INFORMATION

Description: Master Paint Remover is a product based on methylene chloride. The product is a thick fluid, but is easy to use. Paint Remover is not recommended to be used in linoleum or vinyl coating.

Recommended Use: It is suitable for all surfaces should be dry and free from dust and other contamination prior to use.

PHYSICAL CONSTANTS:

Pack Size: 00.91 LTR, 03.64 LTR OR 04.00 LTR

Colour: None

Spreading rate : **Good**

Solids (% by volume): **7+2**

Specific Gravity: 1.25 + 0.05

Viscosity: Semi Paste

Physical constants are subject to normal manufacturing tolerances

APPLICATION DETAIL :

Application Method : Brush, putty knife

Thinner : Master NC Thinner (For Cleaning)

Thinning : Single Pack (Ready To use)

No. of Coats : Apply on to the surface in a rather thick coat (2.5mm)

TYPICAL SURFACES:

New Surfaces: The surface should be dry and free from dust and other contamination prior to use.

Previously painted surfaces: Paint Remover is most efficient at approximately 20oC. Not to be exposed to temperature above 35oC. Avoid inhalation of gasses.



Storage As there is a possibility of pressure being formed in the tin when the product is stored, a cloth should be placed over the lid in order to hold it back when the tin is opened.

Handling Spray under Well-Ventilated conditions. Do not breathe or inhale mist. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately.

SAFETY AND ENVIRONMENTAL NOTES:

FIRST-AID MEASURES

Remove affected person from source of contamination. Get medical attention immediately!

INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung edema (shortness of breath) may develop up to 24 hours after exposure. Bring these instructions. Place unconscious person on the side in the recovery position and ensure Breathing can take place.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to Hospital or eye specialist.

Disclaimer:

The information given in this data sheet is to the best of our knowledge based on laboratory testing and practical experience. However, as the product is often used under conditions beyond our control, we cannot guarantee anything but the quality of the product itself. We reserve the right to change the given data without notice.

