



## NC CLEAR LACQUER

### Material Safety Data Sheet

NC Clear Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent Gloss finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high Gloss finish is required.

**Research and Development Department**  
**Master Paint Industries (Pvt.) Ltd.**  
**Phone : 0 4 2 – 111 – 333 – 465,**  
**E-Mail : [info@masterpaints.com](mailto:info@masterpaints.com)**



**PRODUCT INFORMATION**

Description: NC Clear Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent Gloss finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high Gloss finish is required.

**TECHNICAL INFORMATION:**

|                   |                                      |
|-------------------|--------------------------------------|
| Colour            | Clear                                |
| Finish            | High Gloss                           |
| Generic Type      | NC                                   |
| Vol Solid         | 37 %                                 |
| Spreading Rate    | 12.3 m <sup>2</sup> / L. @30 µm dft. |
| Drying Time       | 15 min. at 30 °C.                    |
| Recoating Time    | 1 hr.                                |
| Thinner / cleaner | NC Thinner                           |
| Weight / Litre    | 0.9 – 1.0 kg.                        |
| Flash Point       | 40 °F                                |
| Further coat      | Coat on coat                         |
| Packing size      | 0.91 and 3.64 litres.                |

**APPLICATION DETAIL :**

Conventional or airless spray.

**TYPICAL SURFACES :**

Pre- primed and smooth surface. Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood or steel should be properly sanded and must be scuffed in the direction of wood grains. Seal with NC Sealer.

**SAFETY AND ENVIRONMENTAL NOTES:**

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

