



N.C MATT LACQUER

Material Safety Data Sheet

NC Matt Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent matt finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high matt finish is required.

Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com



PRODUCT INFORMATION

Description: NC Matt Lacquer is a protective and decorative nitrocellulose based lacquer which provides hard, scratchproof, smooth and transparent matt finish. Formulated as a topcoat on NC paint systems where fast drying, hard and clear high matt finish is required.

TECHNICAL INFORMATION:

Colour	Clear
Finish	Matt
Generic Type	NC
Vol Solid	37 %
Spreading Rate	12.3 m ² / L. @30 µm dft.
Drying Time	15 min. at 30 °C.
Recoating Time	1 hr.
Thinner / cleaner	NC Thinner
Weight / Litre	0.9 – 1.0 kg.
Flash Point	40 °F
Further coat	Coat on coat
Packing size	0.91 and 3.64 litres.

APPLICATION DETAIL :

Conventional or airless spray.

TYPICAL SURFACES :

Pre- primed and smooth surface. Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood or steel should be properly sanded and must be scuffed in the direction of wood grains. Seal with NC Sealer.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

