



N.C PUTTY

Material Safety Data Sheet

N.C Putty NC based Car refinishing Product/ Knife filler Master is recommended for fast and efficient re-finishing. This product is recommended for all motor vehicles.

**Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com**



PRODUCT INFORMATION

Description: N.C Putty NC based Car refinishing Product/ Knife filler Master is recommended for fast and efficient re-finishing. This product is recommended for all motor vehicles.

TECHNICAL INFORMATION:

Colour	Grey
Finish	Matt
Generic Type	NC
Vol Solid	40 %
Spreading Rate	5 m ² / L. @ 75 µm dft.
Drying Time	20 - 30 min. at 30 °C.
Recoating Time	2-3 hrs.
Thinner / cleaner	NC Thinner
Weight / Litre	1.40 - 1.5 kg.
Flash Point	40 °F
Further coat	NC topcoats / Primers.
Packing size	01 KG,04KG

APPLICATION DETAIL :

Mask surface and apply filler firmly into place with a putty knife. Fill up slightly higher surface to allow for sanding. Sand after drying on shallow repairs, deep repairs after 2-8 hours. Use medium sand paper; do not continue high speed sanding.

TYPICAL SURFACES :

Prepared or smooth surface .Ensure surface is dry, clean and free from contaminant.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

