



N.C SANDING SEALER

Material Safety Data Sheet

NC Sealer is a protective nitrocellulose based quick drying sanding sealer. It provides smooth and excellent base to top coat application.

**Research and Development Department
Master Paint Industries (Pvt.) Ltd.
Phone : 0 4 2 – 111 – 333 – 465,
E-Mail : info@masterpaints.com**



PRODUCT INFORMATION

Description: NC Sealer is a protective nitrocellulose based quick drying sanding sealer. It provides smooth and excellent base to top coat application.

TECHNICAL INFORMATION:

Color	Milky white , dried film transparent.
Finish	Silk
Generic Type	NC
Vol Solid	35 %
Spreading Rate	14 m ² / L. @25 µm dft.
Drying Time	15 min. at 30 °C.
Recoating Time	1 hr.
Thinner / cleaner	NC Thinner
Weight / Litre	0.9 – 1.0 kg.
Flash Point	40 °F
Further coat	NC based top coats.
Packing size	0.91 and 3.64 litres.

APPLICATION DETAIL :

Conventional or airless spray.

TYPICAL SURFACES :

Pre- primed and smooth surface. Ensure that surface is clean, dry and free from grease, oil and other contamination. Wood should be properly sanded and must be scuffed in the direction of wood grains.

SAFETY AND ENVIRONMENTAL NOTES:

Ensure proper ventilation during application and drying of paint. Avoid inhalation of paint mist and vapours and skin contact. Spillage of paint on skin should immediately be removed with suitable cleanser soap and water. Eyes should be well flushed with water and immediate medical attention should be sought.

